




标记	处数	更改内容	版本	签名	时间



Motor parameters	
Model	U20035
Voltage	48V DC
Rated output (W)	503.04
Rated torque (Nm)	24
Instant max torque (Nm)	50
Rated current (Arms)	18
Instant max current (Arms)	40
Rated speed (Rpm)	200
Max speed (Rpm)	400
Torque parameters (Nm/Arm)	1.33
Rotor inertia (10^{-4}kg.m^2)	41
Back EMF coefficient (V/krpm)	100
Coil resistance (Ω)	0.2
Phase inductance (mH)	0.44
Number of pole-pairs (2P)	13



基本尺寸	选用等级				角度
	A	B	C	D	
<5	± 0.02	± 0.03	± 0.05		$0^\circ \sim 30^\circ$ $\pm 0.1^\circ$
>5~20	± 0.03	± 0.05	± 0.1		$31^\circ \sim 60^\circ$ $\pm 0.3^\circ$
>20~50	± 0.05	± 0.1	± 0.15		$61^\circ \sim 90^\circ$ $\pm 0.5^\circ$
>50~100	± 0.1	± 0.15	± 0.2		
>100	$\pm 0.1\%$	$\pm 0.15\%$	$\pm 0.2\%$		

料号	U20035	描述	20035电机		
材料		图幅	数量	比例	
		A3	1	2:1	
版本	A1	第 1 张 共 1 张			
设计	戴耿志	强和电机			
审核					
批准	戴耿志				